



**SPECIFICATIONS:**

**ELECTRICAL:** 120VAC/1PH/60Hz/1Amp  
(POWER SUPPLY INPUT)  
(POWER SUPPLY OUTPUT/TIMER INPUT  
12VDC / 2 Amps)

**VALVE CONNECTIONS:** 1.5" NPT (f)

**MAXIMUM PRESSURE:** 200 PSI @ 70 DEG.F

**ACTUATION TIME:** 3 SECONDS

**CONTROL:** SELECTABLE - AUTO/OFF/MANUAL  
AUTO - TIMED FLUSH, ADJUSTABLE INTER-  
VAL(OFF) AND DURATION(ON)  
(SW POSITION MAINTAINED)  
MANUAL - MOMENTARY FLUSH OPERATION  
WITH SWITCH PRESS

**ENCLOSURE:** NEMA4X DERATED TO NEMA3R

**VALVE BODY MATERIAL:** NYLON  
**VALVE BALL MATERIAL:** STAINLESS STEEL

**PRODUCT SPECIFICATION**

**MILLER LEAMAN** INC

800 Orange Ave. Daytona Beach FL 32114

DRAWN	DMP	1/08/2016
CHECKED		
ENG APPR.		
MKT APPR.		
SHEET 1 of 1	Ref: ML22069	Rev:

TITLE:	Automatic Timer Flush Package ATF-EA-1.5
--------	--

**Fischer-Robertson, Inc.**  
3890 Symmes Road  
Hamilton, OH 45015  
Ph 513-860-3445 Fx 513-860-4744  
[www.fischer-robertson.com](http://www.fischer-robertson.com)