



BEVCHECK & BEVCHECK PLUS

Integrity Test Units



Monitoring performance and product quality

Simple routine integrity testing for the beverage industry.

BEVCHECK

The BEVCHECK is an easy to use, portable unit that allows you to test the integrity of your membrane filters using the pressure decay method. Test data can be reported as pressure decay or diffusional flow.

BEVCHECK is a small hand held unit, or is light enough to be mounted directly on to a connection on the filter housing. Software included with the unit enables it to be connected to a PC for enhanced programming and data handling flexibility.

BEVCHECK PLUS

The BEVCHECK PLUS provides an automated method for testing membrane filter cartridges used in beverage applications. Using the pressure decay method, the unit controls the whole test from increase of pressure, through stabilization and pressure decay measurement, to release of pressure.

Test data can be reported as pressure decay or diffusional flow and is provided in a printed summary. The unit is small enough to be portable around the production facility, or can be positioned centrally for remote connection to the filter housings.



BEVCHECK & BEVCHECK PLUS

Integrity Test Units

- Large memory stores up to 19 programs and 100 test reports
- Flexible - suitable for use with compressed air or nitrogen
- Accommodates a wide range of filter retention ratings and housing sizes
- Clear liquid crystal display and wipe clean keypad
- Self test function automatically checks the function of the unit
- PC interface and software provides additional programming and data handling flexibility
- IP53 protection class
- Hand held portability with rechargeable battery operation
- Convenient built-in printer provides printed test report (PLUS)



FISCHER-ROBERTSON, INC.
FILTRATION & SEPARATION

(513) 860-3445 | Sales@fischer-robertson.com



Physical Parameters

	BEVCHECK	BEVCHECK PLUS
Housing Material.....	ABS	Polystyrol
Instrument Size.....	(WxDxH) 105 mm x 210 mm x 45 mm (4" x 8.25" x 1.75")	(WxDxH) 315 mm x 280 mm x 150 mm (12.5" x 11" x 6")
Weight.....	0.5 Kg (1.1 lbs)	3.9 Kg (8.6 lbs)
Ingress Protection Class.....	IP53	IP53
Power Supply.....	Re-Chargeable HiMH Battery (4.8 V / 1.5 Ah) & External Charger (100- 230V AC / 47 - 63 Hz / 7.5V 1.33A) 7 hours Typ.	HiMH Battery (4.8 V / 1.5 Ah) & External Charger / Mains (230V AC:18V DC, 1.7A / 230V AC:15V AC, 15VA) 2 hours Typ.
Battery Life (From Full Charge).....	16 Key - Polycarbonate Keypad	16 Key - Polycarbonate Keypad
Keyboard.....	0 - 4000 mbar	0 - 4500 mbar
Inlet Pressure Required.....	3 - 33 °C (37.4 - 91.4 °F)	3 - 30 °C (37.4 - 95 °F)
Operation Temperature.....	Compressed Air / Filter : Rectus 21 Male	Compressed Air / Filter : Festo 4 mm Stäubli RBE03 Male Vent : Festo 4 mm
Pneumatic Connectors.....	3 - 35 °C (37.4 - 95 °F)	3 - 35 °C (37.4 - 86 °F)
Storage Temperature.....	5 - 95% Rel.	5 - 95% Rel.
Ambient Humidity.....	LCD - 16 Character x 2 Lines	LCD - 20 Character x 4 Lines
Display.....	None	Built in Thermal Printer - 57 mm Printer
Printer.....	English, German, Italian, French, Spanish & Portugese	English, German, Italian, French, Spanish & Portugese
Language.....	19	19
Storable Test Programs.....	100	100
Storable Test Records.....	Manual (Additional Accessory Kit Required)	Fully Automatic
Test Pressure Control.....	0 - 4000 mbar	0 - 3900 mbar
Test Pressure Range.....	10 - 999999 ml	10 - 999999 ml
Housing Volume Range.....	1 - 99.9 ml / min	1 - 999.9 ml / min
Diffusional Flow Range.....	1 - 1800 secs	1 - 1800 secs
Stabilisation Time Range.....	1 - 1800 secs	1 - 1800 secs
Test Time Range.....	PC Data / Remote Operation : RS232 4-Pole Jack	D-Sub 25 Pole PC Data / Remote Operation : RS232 9-Digit Male
Interfaces.....	CE Declaration of Conformity	CE Declaration of Conformity
Documentation / Ancillaries.....	Calibration Certificate	Calibration Certificate
	Winfilter PC Software	Winfilter PC Software
	Power Supply / Charger with Country Specific Mains Adaptor	Power Supply / Charger with Country Specific Mains Adaptor
	PC Comms Cable (RS232 - 4 Pole Jack to 9 Pin Male)	PC Comms Cable (RS232 - 4 Pole Jack to 9 Pin Male)
	Installation, Operation & Maintenance Instructions (IOMI)	Installation, Operation & Maintenance Instructions (IOMI)
	Foam Lined Carry Case	Foam Lined Carry Case

Ordering Information

	BEVCHECK	BEVCHECK PLUS
Model.....	WBC-230	WBC-BEVCHECK PLUS
Calibration order code.....	609500028	609500091