SAP Free Water Barriers for Aviation Fuel

CDFX[™] Series 2" OD EI-1588 2nd Edition Qualified Water Barrier Elements for Aviation Fuel Filtration

Next Generation Water Barrier Elements:

Since the introduction of aviation fuel monitor cartridges in aviation fueling, super absorbent polymers (SAP) have been the essential materials used in the final stage of airport ground fueling systems for protection of onboard systems from water contamination. The material's ability to absorb and chemically lock in water have it's challenges—potential media migration downstream.

Parker Velcon CDFX water barrier technology eliminates the uncertainty of SAP migration downstream by removing SAP from the equation while still providing the efficiency and water removing performance you can rely on as a drop-in replacement element.

Contact Information:

Fischer-Robertson, Inc. 3890 Symmes Road Hamilton, OH 45015 ph 513-860-3445 fx 513-860-4744 www.fischer-robertson.com

Product Features:

• INNOVATIVE BARRIER TECHNOLOGY

Water and dirt are prevented from passing downstream allowing only clean dry fuel

- EI 1588 PERFORMANCE Defense against emulsified water and full water slug protection
- COST AND RESOURCE EFFICIENT Fits currently deployed monitor housings without the need for costly retrofitting or addition of electronic sensors

NO MORE MEDIA MIGRATION CONCERNS

Zero uncertainties about SAP media extrudables migration or downstream and in filtration systems

 COMPATIBLE MATERIALS Utilizes industry known materials of construction









Barrier Technology

The new barrier technology provides a dropin solution for existing 2" diameter filter monitors. Exterior dimensions and endcap styles remain the same while SAP media is replaced with new barrier technology. This allows for use with current monitor housings without the need for expensive and costly retrofitting of filtration systems on fueling carts and fueling trucks.

Our barrier technology is:

- Effective against low-water emulsions
- Effective against total water submersion
- Effective when introduced to water slugs at or greater than 101.5 psid (7 bar)
- Effective in fuel with FSII (anti-icing additive)
- Excellent dirt efficiency

HOW OUR NEW BARRIER TECHNOLOGY WORKS

Our barrier technology filters contaminate and prevents water from passing downstream.

Water droplets are blocked by a hydrophobic material that is porous to provide clean, dry fuel.

Water droplets impeded on the surface of the media coalesce and drop to the bottom of the vessel from where they must be drained.



Cartridge	Velcon Model	Overall	Replacement for:		
Flow Rate	Number	Length	Velcon SAP	Facet SAP	Faudi DDF
USGPM		(inches)	Monitor	Monitor	Model
			Model No.	Model No.	Number
5	CDFX-205B	5 13 / 16	CDF-205P	FG-205-7	
10	CDFX-210B	10 13 / 16	CDF-210P	FG-210-7	DDO2.2-10-2
15	CDFX-215B	15 13 / 16	CDF-215P	FG-215-7	DDO2.2-15-2
20	CDFX-220B	20 13 / 16	CDF-220P	FG-220-7	DDO2.2-20-2
25	CDFX-225B	25 13 / 16	CDF-225P	FG-225-7	
30	CDFX-230B	30 13 / 16	CDF-230P	FG-230-7	DDO2.2-30-2

Filter Element Selection

© 2022 Parker Hannifin Corporation

VEL2296R4 0323

Fischer-Robertson, Inc. 3890 Symmes Road Hamilton, OH 45015 ph 513-860-3445 fx 513-860-4744 www.fischer-robertson.com

